




AMERICAN FLOOR PRODUCTS COMPANY, INC.

AFCO-USA

P.O. BOX 7055 • Gaithersburg, Maryland 20898 -7055 • 301-987-0490 • Fax 301-987-0422
 email: sales@afco-usa.com • Web Site: www.afco-usa.com

CUSTOMER P.O. #

VENUS[®] One Piece Partition End Guard (CG-2130)



VENUS[®] One Piece Partition End Guard (CG-2130)

Mounting	Application	Shock absorbing	Construction	Materials	Fire rating
Flush	High abuse	25.4 ft.lbs/in. ASTM D-256	New	Vinyl Aluminum	Class A

Testing in accordance with NFPA 255 (ASTM E 84):

Class A

Flame Spread Index: 5

Smoke Developed Index: 185

<p>Features:</p> <ul style="list-style-type: none"> • Class A fire rating • Stock lengths: 8'-0" (2438 mm), 9'-0" (2743 mm) and 10'-0" (3048 mm) • Custom cut lengths available • Available with aluminum cove base insert for use with vinyl cove base standard in 4" (102 mm) and 6" (152 mm) heights 	<p>Finishes:</p> <p>Vinyl cover</p> <ul style="list-style-type: none"> • Manufacturer's standard colors • Custom colors available <p>Aluminum retainer</p> <ul style="list-style-type: none"> • Mill finish aluminum
--	--

Corner Guard designs conform to OSHA, ANSI Life Safety, NFPA, BOCA, UBC, BOMA, ICBO, SBCCI, American Disabilities Act Accessibility Guidelines and all National Building /Code requirements.

	ITEMS	QUANTITY
JOB NAME:		
JOB NUMBER:	Guard Length: 8', 9' or 10'	
CONTRACTOR:	Color:	
ARCHITECT:	Finished Partition Width:	
DEALER NAME:	Cove Base Insert:	
SIGNATURE:	Date:	